



Application	Safety device to mitigate suspension trauma
Fitment	a. Unit supplied separately as a component b. Select anchor point on harness at waist c. Loop unit around harness strap d. Feed back through webbing eye e. Allow unit to hang freely from waist
To deploy	f. Pull connector downward to release step g. Pull step out of cover until fully deployed h. Feed connector back through webbing i. Hook connector onto a webbing eye j. Insert foot (or both feet) into harness step
Adjustment	k. Remove foot (or feet) from harness step l. Move connector to another webbing eye m. Insert foot (or both feet) into harness step
Be aware	Training is required to use this device

Component

- Primary webbing
- Webbing tabs
- Buckle
- Heat shrink
- Label
- Yarn

Material properties

- Polyester 44mm wide with breaking strength of 22kN
- Black 25mm webbing
- Alloy steel clasp buckle so suit 25mm webbing
- 57mm heat shrink sleeve
- Printed full colour paper
- Polyester thread with colour contrasting to webbing colour

Product standards N/a

Conforms to N/a

Manufacturer Hilsen, PO BOX 890177, Lyndhurst, Johannesburg, 2106

Permit numbers 10853/17054, 10853/17064, 10853/17055

Disclaimer and product limitations

Maximum weight of user (including clothing, PPE and tooling) is 100kg up to Fall Factor 1, and 120kg up to Fall Factor 2.

Adequate training on correct use of this equipment must be provided to the user by a competent person before this equipment is issued for use. Simply reading the equipment user instructions does not suffice as adequate training. This equipment must not be used by a person with any medical condition that could affect their safety when using the equipment in normal or emergency use. It is recommended that at least every three months the fall arrest system (or component) or other equipment be inspected by a competent person. This equipment is intended to be used for 'fall arrest', 'work restraint' and/or 'rope access' as indicated. This equipment is not intended to be used for any other purpose other than indicated and may not be used outside of its limitations. This equipment becomes obsolete 5 years from manufacture date, regardless of the condition of the equipment. This equipment must be used strictly in accordance with the instructions given and without deviation. This equipment is used entirely outside of the manufacturer's control and accordingly the manufacturer cannot be held liable for any loss, claim or liability arising from any failure of this equipment from any cause whatsoever.