



Application	Fall arrest Vertical fall arrest system attachment Work positioning
Attachment	Dorsal position (for fall arrest) Frontal belay loops (for partial fall arrest) On waist belt (for work positioning)
Kit Contents	a. Performance harness (4-point) b. Lanyard SC2 (carabiner connector) c. Work positioning lanyard (webbing type) d. Open round sling 60cm e. Open round sling 120cm f. Gear bag 50
Options	Order an additional Harness PPE Pack (short brim helmet with chin strap, work gloves), not supplied as standard



SANS 50361:2003 Full body harnesses, SANS 50355:2003 Energy absorbers, SANS 50354:2003 Lanyards; conforms to SANS 50358:2008 Work positioning, SANS 50362:2008 Connectors, SANS 50566:1997 Slings

Component

Primary webbing	Polyester 44mm wide with breaking strength of 22kN
Steel dee ring	Breaking strength of 3 ton
Standard buckle	Alloy steel 2/3 bar buckle so suit 44mm webbing
Plastic insert	Polypropylene molded insert
Hook	Steel double action scaffold hook (2) and snap hook (1) with breaking strength of 22kN
Tear webbing	Polyester 44mm wide manufactured to perform to SANS 50355:2003 Energy absorbers
Heat shrink	Clear plastic sleeve 67mm
Yarn	Polyester thread with colour contrasting to webbing colour
Protective sleeve	High pressure lay flat hose
Carabiner	Alloy steel screw gate carabiner
Label	Textile material 40mm wide with thermal transfer
Bag fabric	550gsm heavy duty PVC
Sling webbing	Polyester 25mm with breaking strength 10kN
Floating buckle	Alloy steel floating buckle so suit 44mm webbing

Product standards SANS 50361:2003 Full body harnesses, SANS 50355:2003 Energy absorbers, SANS 50354:2003 Lanyards

Conforms to SANS 50358:2008 Work positioning, SANS 50362:2008 Connectors, SANS 50566:1997 Slings

Manufacturer Hilsen, PO BOX 890177, Lyndhurst, Johannesburg, 2106

Permit numbers 10853/17054, 10853/17064, 10853/17055

Disclaimer and product limitations

Maximum weight of user (including clothing, PPE and tooling) is 100kg up to Fall Factor 1, and 120kg up to Fall Factor 2.

Adequate training on correct use of this equipment must be provided to the user by a competent person before this equipment is issued for use. Simply reading the equipment user instructions does not suffice as adequate training. This equipment must not be used by a person with any medical condition that could affect their safety when using the equipment in normal or emergency use. It is recommended that at least every three months the fall arrest system (or component) or other equipment be inspected by a competent person. This equipment is intended to be used for 'fall arrest', 'work restraint' and/or 'rope access' as indicated. This equipment is not intended to be used for any other purpose other than indicated and may not be used outside of its limitations. This equipment becomes obsolete 5 years from manufacture date, regardless of the condition of the equipment. This equipment must be used strictly in accordance with the instructions given and without deviation. This equipment is used entirely outside of the manufacturer's control and accordingly the manufacturer cannot be held liable for any loss, claim or liability arising from any failure of this equipment from any cause whatsoever.