



Application	Rope access Not to be used for fall arrest!
Attachment	Connector on waist (for rope access)
Other features	Padded waist Padded legs Gear loops on waist
Adjustment	Waist belt (standard buckles) Leg straps (standard buckles)
Sizing	Small, medium, large, XL and 2XL



Conforms to SANS 50813:1997 Sit harness

Component

- Primary webbing
- Steel dee ring
- Standard buckle
- Yarn
- Label
- Padding
- Quick release buckle
- Gear loop

Material properties

- Polyester 44mm wide with breaking strength of 22kN
- Breaking strength of 3 ton
- Alloy steel 2/3 bar buckle so suit 44mm webbing
- Polyester thread with colour contrasting to webbing colour
- Textile material 40mm wide with thermal transfer
- High density foam padding 6mm
- Alloy steel bayonet type buckle
- Webbing loop 25mm with tubular PVC sleeve

Product standards N/a

Conforms to SANS 50813:1997 Sit harness

Manufacturer Hilsen, PO BOX 890177, Lyndhurst, Johannesburg, 2106

Permit numbers 10853/17054, 10853/17064, 10853/17055

Disclaimer and product limitations

Maximum weight of user (including clothing, PPE and tooling) is 100kg up to Fall Factor 1, and 120kg up to Fall Factor 2.

Adequate training on correct use of this equipment must be provided to the user by a competent person before this equipment is issued for use. Simply reading the equipment user instructions does not suffice as adequate training. This equipment must not be used by a person with any medical condition that could affect their safety when using the equipment in normal or emergency use. It is recommended that at least every three months the fall arrest system (or component) or other equipment be inspected by a competent person. This equipment is intended to be used for 'fall arrest', 'work restraint' and/or 'rope access' as indicated. This equipment is not intended to be used for any other purpose other than indicated and may not be used outside of its limitations. This equipment becomes obsolete 5 years from manufacture date, regardless of the condition of the equipment. This equipment must be used strictly in accordance with the instructions given and without deviation. This equipment is used entirely outside of the manufacturer's control and accordingly the manufacturer cannot be held liable for any loss, claim or liability arising from any failure of this equipment from any cause whatsoever.