



Application	Fall arrest Work positioning
Attachment	Dorsal position (for fall arrest) On waist belt (for work positioning)
Other features	Padding over shoulders Padded leg straps Rescue handles on shoulders Fitted with a standing step
Adjustment	Leg straps (standard buckles) Chest strap (standard buckle) Shoulder straps (standard buckles)
Sizing	Small, medium, large, XL and 2XL
Lanyard set	Pair with lanyard per site requirements Cost and order your lanyard set separately



SANS 50361:2003 Full body harnesses; conforms to SANS 50358:2008 Work positioning

Component

- Primary webbing
- Steel dee ring
- Standard buckle
- Quick release buckle
- Plastic insert
- Carabiner
- Yarn
- Label
- Padding

Material properties

- Polyester 44mm wide with breaking strength of 22kN
- Breaking strength of 3 ton
- Alloy steel 2/3 bar buckle to suit 44mm webbing
- Alloy steel bayonet type buckle to suit 44mm webbing
- Polypropylene molded insert
- Steel screwgate carabiner with breaking strength of 22kN
- Polyester thread with colour contrasting to webbing colour
- Textile material 40mm wide with thermal transfer
- High density foam padding 6mm

Product standards	SANS 50361:2003 Full body harnesses
Conforms to	SANS 50358:2008 Work positioning
Manufacturer	Hilsen, PO BOX 890177, Lyndhurst, Johannesburg, 2106
Permit numbers	10853/17054, 10853/17064, 10853/17055

Disclaimer and product limitations

Maximum weight of user (including clothing, PPE and tooling) is 100kg up to Fall Factor 1, and 120kg up to Fall Factor 2.

Adequate training on correct use of this equipment must be provided to the user by a competent person before this equipment is issued for use. Simply reading the equipment user instructions does not suffice as adequate training. This equipment must not be used by a person with any medical condition that could affect their safety when using the equipment in normal or emergency use. It is recommended that at least every three months the fall arrest system (or component) or other equipment be inspected by a competent person. This equipment is intended to be used for 'fall arrest', 'work restraint' and/or 'rope access' as indicated. This equipment is not intended to be used for any other purpose other than indicated and may not be used outside of its limitations. This equipment becomes obsolete 5 years from manufacture date, regardless of the condition of the equipment. This equipment must be used strictly in accordance with the instructions given and without deviation. This equipment is used entirely outside of the manufacturer's control and accordingly the manufacturer cannot be held liable for any loss, claim or liability arising from any failure of this equipment from any cause whatsoever.