



Application	Fall arrest (work at height from roof)
System	Portable vertical or horizontal access system, secure a ladder for roof work
Contents	a. Anchor sling 200cm (4) b. Daisy chain 200cm (8) c. Oval maillon 10mm (12) d. Crown protectors (2) e. Carabiners (12) f. Gear bag 50
Training for user	Required training: Unit Standard ID: 229998 Explain and perform fall arrest techniques when working at heights
Training installer	Required: Unit Standard ID: 229995 Install, use and perform basic rescues from fall arrest systems and implement fall protection plan
Be aware	Requires a harness with frontal attachment point



Conforms to SANS 50362:2008 Connectors, SANS 50795:1996 Anchor devices, Construction Regulations 10 (5) (e)

Component

- Webbing
- Webbing
- Steel dee ring
- Floating buckle
- Carabiner
- Oval Maillon
- Strap webbing
- Yarn
- PVC fabric
- Label

Material properties

- Polyester 44mm wide with breaking strength of 22kN
- Polyester 75mm wide with breaking strength of 22kN
- Breaking strength of 3 ton
- Alloy steel floating buckle so suit 44mm webbing
- Alloy steel screw gate carabiner
- 8mm oval maillon
- Black 50mm polypropylene webbing
- Polyester thread with colour contrasting to webbing colour
- Heavy duty PVC fabric 550gsm
- Textile material 40mm wide with thermal transfer

Product standards N/a

Conforms to Conforms to SANS 50362:2008 Connectors, SANS 50795:1996 Anchor devices, Construction Regulations 10 (5) (e)

Manufacturer Hilsen, PO BOX 890177, Lyndhurst, Johannesburg, 2106

Permit numbers 10853/17054, 10853/17064, 10853/17055

Disclaimer and product limitations

Maximum weight of user (including clothing, PPE and tooling) is 100kg up to Fall Factor 1, and 120kg up to Fall Factor 2.

Adequate training on correct use of this equipment must be provided to the user by a competent person before this equipment is issued for use. Simply reading the equipment user instructions does not suffice as adequate training. This equipment must not be used by a person with any medical condition that could affect their safety when using the equipment in normal or emergency use. It is recommended that at least every three months the fall arrest system (or component) or other equipment be inspected by a competent person. This equipment is intended to be used for 'fall arrest', 'work restraint' and/or 'rope access' as indicated. This equipment is not intended to be used for any other purpose other than indicated and may not be used outside of its limitations. This equipment becomes obsolete 5 years from manufacture date, regardless of the condition of the equipment. This equipment must be used strictly in accordance with the instructions given and without deviation. This equipment is used entirely outside of the manufacturer's control and accordingly the manufacturer cannot be held liable for any loss, claim or liability arising from any failure of this equipment from any cause whatsoever.