

### Product: Performance Harness (2 Point)

Code: 8.37C

**Conformance Standards:** SANS 50361:2003 Full body harnesses

**Product limitations:** The system is suitable for users up to 100kg in mass, including the mass of the user, their apparel and any equipment attached to their person, without restriction. Users with a mass exceeding 100kg but less than 120kg must attach the fall arrest system at fall factor 1, or above. Users with a mass exceeding 120kg but less than 140kg must attach the fall arrest system at fall factor 0.5 or above.

**Application:** Fall arrest and vertical fall arrest system attachment

**Hard points:** Dorsal position (for fall arrest), frontal position (for partial fall arrest and vertical fall arrest system attachment)

**Features:** Easy to fit, lightweight, full adjustment

**Padding:** Dorsal point and leg straps are padded

**Adjustments:** Interlocking buckles on leg, chest and shoulder straps

**Lanyard set:** The Performance Harness is supplied separately and can be paired with a suitable *Hilsen* Lanyard Set

**Sizing:** Available in sizes small to 2XL (see the *Hilsen* Sizing Guide for more information)

**Optional extras:** Step Device (Code 8.35 or 8.35B) Gear Bag 50 (Code 3.03)



The Performance Harness is supplied separately and can be paired with a suitable *Hilsen* Lanyard Set

**Disclaimer:** Adequate training on correct use of this equipment must be provided to the user by a competent person before this equipment is issued for use, as applicable. Simply reading the equipment user instructions does not suffice as adequate training. This equipment must not be used by a person with any medical condition that could affect their safety when using the equipment in normal or emergency use. It is recommended that at least every three months a fall arrest system (or component thereof) be inspected by a competent person. This equipment may be intended to be used for 'fall arrest', 'work restraint' and/or 'rope access' as indicated. This equipment is not intended to be used for any other purpose other than indicated and may not be used outside of its limitations. Fall arrest equipment becomes obsolete 10 years from manufacture date, regardless of the condition of the equipment. This equipment must be used strictly in accordance with the instructions given and without deviation. This equipment is used entirely outside of the manufacturers control and accordingly the manufacturer cannot be held liable for any loss, claim or liability arising from any failure of this equipment from any cause whatsoever.

For more information and full product range: [www.hilsen.co.za](http://www.hilsen.co.za)